

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/087883 A1(51) International Patent Classification⁷: G01V 3/24

(21) International Application Number: PCT/EP03/50101

(22) International Filing Date: 10 April 2003 (10.04.2003)


(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02290967.5 17 April 2002 (17.04.2002) EP(71) Applicant (for FR only): SERVICES PETROLIERS
SCHLUMBERGER [FR/FR]; 42 rue Saint Dominique,
F-75007 Paris (FR).(71) Applicant (for JP, NL only): SCHLUMBERGER
HOLDINGS LIMITED [—/—]; PO BOX 71, Craigmuir
Chambers, Road Town, Tortola (VG).(71) Applicant (for CA, GB only): SCHLUMBERGER
CANADA LIMITED [CA/CA]; 24th Floor - MonencoPlace, 801 6th Avenue SW, Calgary, Alberta T2P 3W2
(CA).(71) Applicant (for BF, BJ, CF, CG, CI, CM, CZ, GA, GN, GQ,
GW, IN, LT, MA, ML, MR, NE, SN, TD, TG, TN, VN only):
PETROLEUM RESEARCH & DEVELOPMENT N.V.
[NL/NL]; De Ruyterkade 26, Willemstad, Curacao (NL).(71) Applicant (for AE, AG, AL, AM, AT, AU, AZ, BA, BB,
BE, BG, BR, BY, BZ, CH, CN, CO, CR, CU, CY, CZ, DE,
DK, DM, DZ, EC, EE, ES, FI, GD, GE, GH, GM, GR,
HR, HU, ID, IE, IL, IS, IT, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LU, LV, MC, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PH, PL, PT, RO, RU, SC, SD, SE, SG, SI, SK,
SL, SZ, TJ, TM, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM,
ZW only): SCHLUMBERGER TECHNOLOGY B.V.
[NL/NL]; Parkstraat 83-89, NL-2514 JG The Hague (NL).(71) Applicant (for CN only): SCHLUMBERGER OVER-
SEAS S.A. [PA/PA]; 8 Calle Aquilino de la Guardia,
Panama City (PA).

[Continued on next page]

(54) Title: PHASE DISCRIMINATION FOR MICRO ELECTRICAL MEASUREMENT IN NON-CONDUCTIVE FLUID



(57) Abstract: A method for electrically investigating a wall of a borehole in a geologic formation including injecting a current into the formation at a first position along the wall and returning the current at a second position along the wall, the formation current having a frequency below about 100 kHz, measuring a voltage in the formation between a third position and a fourth position along the wall, the third and fourth positions being located between the first and second positions, and determining an amplitude of a component of the voltage in phase with the current.

WO 03/087883 A1

BEST AVAILABLE COPY